

Plastecowood's Smartawood Products

Fencing and general installation recommendations.

Thank you for choosing Plastecowood's Smartawood Endurance Plastic Products. For installations please follow these guidelines and recommendations.

Cutting and drilling tools and finishes

Smartawood is extremely tough and durable and is quite abrasive. As a result drill bits and saw blades should be tungsten carbide tipped. Smartawood is made from segregated waste plastic.

Non-plastic contaminants

Plastecowood endeavours to remove as much non-plastic contamination as possible from its input material but occasionally small pieces of metal foil can be incorporated in the profiles, boards and planks.

Personal protective equipment

Appropriate Personal Protective Equipment should be worn when working with Smartawood including safety glasses, gloves, safety boots and ear protection.

Thermal expansion and contraction

Plastic will expand in the heat and contract again when it cools. Where fence rails meet on a post they should not be butted up too tightly but a gap of at least 5 mm should be left between them.

Fence rails will twist in the heat if they expand and they are too tightly joined/ abutted.

Plastecowood Ltd recommends that rails are attached to posts using good quality galvanised mushroom capped bolts which penetrate both the rail and the upright typically with countersunk nuts where appropriate.

The holes can be slightly oversized to allow for expansion and

contraction.

Expansion gaps should also be allowed where Smartawood boards are used for topdecks.

Post installation

Upright posts should be installed so that one third of the post is below ground and two thirds above ground. Consideration should be given, dependent on weight and span of rails and palings and also site-specific application (weather and ground conditions etc.), as to whether posts should be installed with concrete surround below ground.

Post and wire stapling

For post and wire fencing galvanised fencing staples to a maximum of 25mm length can be used but it is important that two pilot holes are drilled first for each staple as the outer surface of Plastecowood's Smartawood product is very tough to penetrate and fencing staples may bounce off with the potential to cause injury. Personal protective equipment should be worn including safety goggles and suitable gloves. Ideally screw fixings should be used instead of hammered nails or staples. Whilst fixing wire to Smartawood may take slightly longer than hammering staples into traditional timber, Plastecowood products will not require further maintenance or replacement for many years beyond the lifetime of traditional timber posts.

Colour and dimensions variation and non-melts

Product dimensions and colour can vary slightly due to nature of process and input material. Plastecowood's input material is low grade waste plastic which means that there is wide variety of different plastics which are reprocessed in Plastecowood's recycling process. Different plastics melt at different temperatures but in order to maintain consistent strength and rigidity, Plastecowood processes at a consistent temperature. for this reason, Plastecowood's Smartawood products will evidence small pieces of non-melt plastic which can be of different colours to the main profile.

Cutting profiles along the length

It should be noted that whilst cutting across a profile i.e. across the shortest section of the profile which does not exceed 150mm, is a standard operation, cutting lengthways along the profile can be problematic, particularly on longer sections. This is because the strength of the profile is in the outside casing which is visible looking 'end-on'. It is likely that removing one side of the "casing" will cause the profile to lose its structural strength and internal tension and bend. On shorter sections for packing or filling this may not be significant to the user but this practice is not recommended where strength and straightness are important.

Environmental awareness

Please also endeavour to collect and dispose of responsibly any loose material resulting from drilling or cutting so as to avoid plastic being lost into the environment.

Smartawood can be recycled at the end of its life by arrangement with Plastecowood Ltd.

Advice and helpline

For advice on installing any of Plastecowood's products please call our helpline on 01745 827000 during office hours which are 0900 to 1600 Monday to Friday.

Plastecowood component guarantee

Plastecowood Ltd offers a 10 year no quibble guarantee for component exchange on all its products, subject to fair wear and tear, users following Plastecowood Ltd.'s installation advice and recommendations, and assuming reasonable care with installation and suitability of product for the application.

Painted products

Where Plastecowood paints products or supplies painted products the paint finish is guaranteed not to peel for a period of two years from delivery of the product. Painted finish is more likely than our

natural finish product to scratch and deteriorate dependent on weather conditions, wear and tear, cleaning methods and cleaning products and whilst we cannot guarantee against such wear and tear the structural strength of the product will not be detrimentally affected.

If in doubt, please ask our helpful sales and technical staff:
01745 827000 info@plastecowood.com.